

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number
WO 03/057071 A2(51) International Patent Classification⁷: A61F

(US). PETROSENKO, Robert [CA/US]; 30 Belmont Place West, Batesville, IN 47006 (US).

(21) International Application Number: PCT/US02/41229

(22) International Filing Date:
20 December 2002 (20.12.2002)

(74) Agent: CONRAD, Richard, D.; Barnes & Thornburg, 11 South Meridian Street, Indianapolis, IN 46204 (US).

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English


(30) Priority Data:
60/344,589 26 December 2001 (26.12.2001) US(71) Applicant (*for all designated States except US*):
HILL-ROM SERVICES, INC. [US/US]; 1069 State Route 46 East, Batesville, IN 47006-9167 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): LOCKWOOD, Jeffrey, S. [US/US]; 500 North Walnut, Batesville, IN 47006(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,

[Continued on next page]

(54) Title: VACUUM BANDAGE PACKING



(57) Abstract: A vacuum bandage (10) is provided for use with a wound (16) having a wound surface (18). The bandage (10) is connectable to a vacuum source (12) and includes a wound dressing member (19) having a wound contacting surface (50), a top surface (70), and a port (60) configured for communication with the vacuum source (12). The wound dressing member (19) further includes holes (74) in the wound contacting surface (50) configured for communication with the wound surface (18) of the wound (16) and a passageway (56, 58) between the port and each hole. The vacuum bandage (10) further includes a pack (30) adjacent to the top surface (70) of the member (19). The pack (30) may include an aperture (32) positioned about the port (60).

WO 03/057071 A2



TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, *ARIPO patent* (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), *Eurasian patent* (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), *European patent* (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), *OAPI patent* (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS,

JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, *ARIPO patent* (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), *Eurasian patent* (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), *European patent* (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), *OAPI patent* (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

-1-

VACUUM BANDAGE PACKING

BACKGROUND OF THE INVENTION

The present disclosure relates to packing for placement over a chronic
5 wound, and particularly to packing for use with a vacuum bandage coupled to a
vacuum source.

Gauze or commercially available foam packing is typically used to
pack a wound. One example is the ALLEVYN® Cavity Wound Dressing available
from Smith & Nephew. This particular wound dressing is made of a polyurethane
10 foam. Gauze is often used to absorb liquid and exudate present on the wound surface.

SUMMARY OF THE INVENTION

The present invention comprises one or more of the following features
or combinations thereof:

15 A bandage for use with a wound and a vacuum source is provided.
The bandage comprises a wound dressing member having a wound contacting surface
and a port configured for communication with the vacuum source. The member
further includes holes formed in the wound contacting surface and configured for
communication with a wound surface of the wound. The member includes a
20 passageway between the port and each hole. The combination may further include a
pack coupled to the top surface of the member. The pack may illustratively include
an aperture positioned about the port of the member. A connector of the member may
be received within the aperture.

In illustrative embodiments, the pack further includes a bottom surface,
25 a top surface, a side wall extending from the top surface to the bottom surface, and a
slit in communication with the aperture. The slit is defined by first and second
confronting interior surfaces which each extend from the top surface of the pack to
the bottom surface and from the aperture to the side wall. The illustrative pack
further includes an adhesive layer coupled to the bottom surface of the pack for
30 coupling the pack to the top surface of the member. The pack may be made of either
open-celled or closed-cell foam.

The member may be generally non-compressible and made of a
medical grade silicone. The member may further include a connector coupled to the

-2-

top surface of the member. Such a connector may be received within the aperture of the pack and configured for communication with the port of the member and the vacuum source.

Other features of the disclosure will become apparent to those skilled in the art upon consideration of the following detailed description of the preferred embodiments exemplifying the best mode of carrying out the disclosure as presently perceived.

BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description particularly refers to the accompanying figures in which:

Fig. 1 is a part perspective, part diagrammatic view of a wound care bandage showing the wound care bandage located on the leg of a patient and coupled to both a vacuum and an irrigation source through the use of a switch valve;

Fig. 2 is an exploded perspective view of the wound care bandage of Fig. 1 showing the bandage positioned above a wound bed and including a wound contacting layer and a cover which cooperate to form a wound dressing member for placement within the wound bed, and also showing a foam packing for placement adjacent the cover and a sealing film to cover the foam packing and member to seal about the wound;

Fig. 3 is a perspective view of the foam packing of the bandage showing the packing having a central aperture and a slit in communication with the aperture and further showing the packing having an adhesive bottom surface for coupling with a top surface of the cover;

Fig. 4 is a sectional view of the bandage showing the member adjacent the wound, the packing adjacent the cover of the member, and a vacuum tube received within the aperture of the packing for coupling with the cover of the member, and further showing the sealing film positioned over the packing and tube to seal to the patient's healthy skin about the wound;

Fig. 5 is a perspective view showing the foam packing of the bandage, the cover of the member, and a horizontal connector of the member coupled to the member to be received within the aperture of the foam packing; and

-3-

Fig. 6 is a perspective view showing the foam packing adjacent to the bandage and further showing the horizontal connector of the member received within the aperture of the packing and showing the vacuum tube coupled to the connector and received within the slit of the packing.

5

DETAILED DESCRIPTION OF THE DRAWINGS

A wound care bandage 10 is provided for use with a vacuum and irrigation source 12, 14, respectively, as shown in Fig. 1. An illustrative vacuum and irrigation source 12, 14 is disclosed in U.S. Patent Publication No.

10 US 2002/0161317 A1 and U.S. Patent No. 6,458,109, both of which are owned by the assignee of the present application and both of which are hereby incorporated herein by reference.

Bandage 10 promotes the healing of a large wound 16 (shown in Figs. 1 and 4) by providing vacuum therapy to the wound 16 to promote blood flow and
15 remove exudate from a wound surface 18 of the wound and by providing for irrigation of the wound 16 with fluids such as saline, for example.

As shown in Fig. 2, wound care bandage 10 comprises a thin, flexible wound dressing member 19. Illustrative wound dressing members are disclosed in U.S. Patent Publication No. US 2002/0082567 A1, which is owned by the assignee of
20 this present application and which is hereby incorporated herein by reference.

Bandage 10 also includes a foam packing 30 above and adjacent member 19, as shown in Figs. 2 and 4. Packing 30 rests on member 19 and includes an aperture 32 for receiving a vacuum tube 34. As shown in Fig. 4, one end of vacuum tube 34 is coupled to member 19 and, as shown in Fig. 1, the other end of
25 tube 34 is coupled to vacuum source 12 and/or irrigation source 14. Bandage 10 further includes a film 40 that is placed over member 19, packing 30, and tube 34 and that attaches to a patient's healthy skin 42 around wound 16. Packing 30 occupies a space between film 40 of bandage 10 and member 19.

Member 19, of bandage 10, is made of a medical grade silicone or
30 other type of elastomer which is pliable. Two companies, for example, which manufacture such medical grade silicone are GE Silicones and NuSil Technology. It is within the scope of this disclosure, however, to include a wound dressing member made of any type of thin, flexible material that is non-porous and non-foam-like. This

-4-

thin, flexible material is also generally non-absorptive. For example, materials such as polyvinylchloride (PVC), PVC free of diethylhexylphthalate (DEHP-free PVC), polyurethane, or polyethylene may be used in the manufacture of member 19.

Further, member 19 may be molded to include anti-microbial constituents. For example, it is within the scope of this disclosure to impregnate member 19 with silver ions which are known anti-microbials. Member 19 is also made of a generally non-adhesive material. Therefore, member 19 does not adhere to the wound surface 18. Further, member 19 is solid in nature and generally non-compressible. For example, when a negative pressure is applied to member 19, a thickness 20 of member 19, as shown in Fig. 4, remains relatively constant. Further, member 19 is generally transparent to enable a caregiver to be able to see the wound 16 through member 19 when member 19 is placed adjacent to wound surface 18. This transparency allows the caregiver to view the progress of the healing of the wound 16. Although packing 30 is placed over member 19, thus preventing a caregiver from viewing the wound surface 18, packing 30 is removable and replaceable without the need to remove member 19 from wound surface 18, as is described below. Therefore, the progress of the healing of wound 16 is viewable through member 19 when the caregiver has removed packing 30 from member 19 to replace with a new packing 30.

As shown in Fig. 2, wound dressing member 19 is illustratively rectangular in shape. However, it is within the scope of this disclosure for member 19 to be any suitable shape. Further, member 19 may be cut to fit any size wound 16. Member 19 includes the combination of a wound contacting layer 22 and a cover 24. Member 19 also includes a connector 26 coupled to cover 24 for communication with vacuum source 12 and/or irrigation source 14. It is also within the scope of this disclosure for connector 26 to be formed integrally with cover 24 or to be a separate piece that is attached to cover 24.

Layer 22 includes a wound contacting surface 50 and an upper or opposite surface 52. Wound contacting surface 50, or portions thereof, contacts and generally conforms to the wound surface 18. Opposite surface 52 includes a central area 54 and a plurality of channels 56 which extend radially away from central area 54, as shown in Fig. 2. Central area 54 is recessed relative to the portions of upper surface 52 between channels 56. As shown in Figs. 2 and 4, channels 56 are open at

-5-

the sides and ends of member 19. Opposite surface 52 further includes concentric channels 58. Central area 54 is provided to communicate with vacuum source 12 and irrigation source 14 through a port 60 of cover 24, as described below.

A plurality of radially extending protrusions or bosses 62 are positioned around central area 54. Bosses 62 are positioned between central area 54 and channels 56, 58, as shown in Fig. 2. Bosses 62 prevent central area 54 from collapsing in on port 60 of cover 24 and forming an unwanted seal which would effectively block air flow through port 60 while suction is applied to bandage 10. Port 60 communicates with the vacuum source 12 and/or the irrigation source 14 via connector 26 and tube 34, as shown in Fig. 2. As mentioned above, port 60 is in communication with central area 54 of layer 22.

Illustratively, four bosses 62 are shown in Fig. 2. However, it is within the scope of this disclosure to provide any number of bosses 62 or the like about central area 54 of layer 22 to prevent central area 54 from sealing off port 60 of cover 24 as suction is applied to bandage 10. Further, it is within the scope of this disclosure to include a boss or bosses 62 having any shape that prevents central area 54 from sealing off port 60 when suction is applied to bandage 10.

Connector 26, as shown in Figs. 2 and 3, is a tubal port coupled to a top surface 70 of cover 24 and in communication with port 60 of cover 24. As mentioned before, it is within the scope of this disclosure for connector 26 to be a separate component of member 19 which is coupled to cover 24 or for connector 26 to be molded integrally with cover 24. Connector 26 includes a vertical passageway 27. Connector 26 connects with tube 34 to provide a vertical tube attachment with respect to port 60. Vertical connector 26 is received within aperture 32 of packing 30. As mentioned above, however, it is within the scope of this disclosure to include a member 19 having only layer 22 and cover 24, without a connector 26, for example. In such an example, tube 34 couples directly to cover 24 for direct communication with port 60. Cover 24 includes a bottom surface 68 and top surface 70, as shown in Fig. 2. Bottom surface 68 engages opposite surface 52 of layer 22, as shown in Fig. 4.

In some embodiments, member 19 is made by heat sealing opposite surface 52 of layer 22 and bottom surface 68 of cover 24 together and by heat sealing connector 26 to top surface 70 of cover 24. Each of connector 26, cover 24 (or the

-6-

combination of cover 24 and connector 26), and layer 22 may be pre-shaped and formed from semi-cured silicone. Once the connector 26, cover 24, and layer 22 are placed together appropriately, the entire member 19 may be heated to heat seal and cure each of the three components to one another. Alternatively, for example, the cover 24 only may be made from semi-cured silicone while the connector 26 and layer 22 may be made from fully cured silicone. Once placed together and heated, connector 26 and layer 22 will heat seal to cover 24. Semi-cured silicone may be bought and pre-molded from a manufacturer such as NuSil Technology, for example. Although the method of heat sealing the cover 24, connector 26, and layer 22 to each other is disclosed, it is within the scope of this disclosure to form member 19 by coupling layer 22, cover 24, and connector 26 together by another suitable means such as through the use of adhesives, for example. Further, it is within the scope of this disclosure to provide a member 19 where cover 24 lies adjacent to, but is not coupled to, layer 22.

As mentioned above, cover 24 is coupled to layer 22 and connector 26 is coupled to cover 24 to form member 19. Cover 24 and layer 22 cooperate to form distinct passageways 72 of member 19 (as shown in Fig. 4) which are defined by channels 56, 58 of layer 22 and bottom surface 68 of cover 24. Passageways 72 are in communication with central area 54 of layer 22 and central area 64 of layer 22 is in communication with port 60 of cover 24 which is in communication with the vacuum and/or irrigation sources 12, 14 via connector 26 and tube 34. Therefore, passageways 72 are in communication with the vacuum and/or irrigation sources 12, 14.

Layer 22 includes through holes 74 which extend from channels 56, 58 through layer 22 to wound contacting surface 50, as shown in Fig. 2. Holes 74 are distinct and are provided to communicate with channels 56, 58 of layer 22. Holes 74 therefore communicate with passageways 72 of member 19 and the vacuum and/or irrigation sources 12, 14 as well to allow the suction from the vacuum source 12 and/or the fluid from the irrigation source 14 to reach the wound surface 18 via the holes 74. Illustratively, holes 74 are 0.020 inch (0.508 mm) in diameter and are spaced approximately 0.500 inch (12.700 mm) apart along channels 56, 58 of layer 22. It is, however, within the scope of the disclosure to include holes having other

-7-

suitable sized diameters and/or other suitable spacing that allow for the removal of exudate without clogging.

Illustrative member 19 of bandage 10 includes a smooth wound contacting surface 50, as shown in Fig. 2. Wound contacting surface 50 may also be ribbed, textured, or roughened. By providing member 19 with a ribbed, textured, or roughened surface, a space is created between surface 50 of layer 22 and wound surface 18. Through holes 74 communicate with this space which permits vacuum source 12 to establish a generally uniformly distributed vacuum or negative pressure to the wound surface 18 to draw blood from the body to the wound surface 18 and to draw exudate from the wound 16 through holes 74, into channels 56, 58 and passageways 72, and out port 60 of cover 24. It is within the scope of this disclosure to include other means for providing a space between surface 50 and wound surface 18 such as providing ribs, protrusions, channels, spacers, etc.

The vacuum or negative pressure which draws blood from the body to the wound surface 18 and draws exudate from the wound 16 up through member 19 promotes the healing of wound 16. As wound 16 heals, granulations form along the wound surface 18. Granulations, therefore, are the replacement within the wound bed of tissue lost. As the granulations fill in the wound bed causing the wound 16 to heal, member 19 rides up on the wound surface 18 on top of the granulations which are formed.

Although illustrative bandage 10 includes one central port 60, it is within the scope of this disclosure to include multiple ports. In order to accommodate different sized wounds 16, member 19 may be trimmed to fit a particular wound 16. Further, some embodiments of member 19 include scale markings. Scale markings indicate areas where a caregiver may trim member 19 to fit a particular wound 16. Further, the scale markings may denote measurement sizes, for example, to permit a caregiver to cut the member 19 to fit a pre-measured wound 16. In order to accommodate various types and placements of wounds on patients, it is within the scope of this disclosure to include a member or members in various conforming shapes and sizes suitable for treating chronic wounds on a patient's heel, abdomen, or sternum, for example.

A switch valve 76 is illustratively provided, as shown in Fig. 1, to allow a user to switch between the use of the vacuum source 12 and the irrigation

-8-

source 14. It will be appreciated that a mechanism other than the switch valve 76 may be used selectively to couple the vacuum source or the irrigation source to the bandage. Simple tube clamps, for example, may be used selectively to open and close the tube set provided with bandage 10. When valve 76 is switched to operate the vacuum source 12, the vacuum suction draws exudate up through the holes 74 and radially inwardly through passageways 72 toward port 60 and finally through tube 34.

Vacuum/irrigation tube 34 extends over the edge of packing 30 and out from under the edge of the sealing film 40. In use, irrigation source 14 delivers liquid through tube 34 and port 60 of cover 24 and into passageways 72 of member 19. The fluid moves radially out through passageways 72 to holes 74. The fluid then moves down through holes 74 to impinge on wound surface 18.

As described above, bandage 10 includes foam packing 30. Foam packing includes a top surface 80 and a bottom surface 82. Illustratively, foam packing 30 is rectangular and sized to match member 19. An adhesive 84 may be attached to bottom surface 82, as shown in Fig. 3. In some embodiments, a silicone-based adhesive is provided on bottom surface 82. Packing 30 may be permanently or temporarily affixed to top surface 80 of member 19 to act as a cavity filler for bandage 10. For example, chronic wounds, such as wound 16, often create a deep cavity. Foam packing 30 is added on top of member 19 to essentially fill the cavity created by the wound. In those embodiments in which packing 30 is temporarily attached to or placed on member 19, packing 30 can be removed and replaced by a caregiver without the need to replace member 19.

As mentioned above, packing 30 includes aperture 32 which extends from top surface 80 to bottom surface 82. Illustratively, aperture 30 is centrally located to receive connector 26 which is centrally located on cover 24 of member 19. It is within the scope of this disclosure for packing 30 to have an aperture which is not centrally located provided that the aperture cooperates with either a connector of member 19 or with a port of the cover of member 19. As shown in Fig. 4, connector 26 is received within aperture 32 of packing 30. A portion of vacuum tube 34 is also received within aperture 32 and couples with connector 26.

As shown in Figs. 2 and 3, packing 30 further includes a slit 86. Slit 86 is defined by first and second confronting interior surfaces 90, 92 which each extend from top surface 80 to bottom surface 82 and are each in communication with

-9-

aperture 32. Surfaces 90, 92 each further extend from aperture 32 to a side wall 88, as shown in Figs. 2 and 3. Slit 86 provides an entryway for tube 34. Slit 86 allows packing 30 to be easily removed and replaced from bandage 10 without the need to disconnect tube 34 from connector 26 or port 60. When removing packing 30 from member 19, tube 34 is slid through slit 86 from aperture 32 to side wall 88. When placing a new packing 30 on member 19, tube 34 is slid through slit 86 from side wall 88 to aperture 32 to rest one end of tube 34 within aperture 32. Because packing 30 is replaceable separately from member 19, member 19 is able to stay in place on wound surface 18 for a longer period of time.

10 In an alternative embodiment shown in Figs. 5 and 6, a horizontal connector 126 is coupled to cover 24. Horizontal connector 126 includes a vertical passageway 127 connected to a horizontal passageway 129. Horizontal connector 126 provides for a horizontal attachment for vacuum tube 34, rather than the vertical attachment shown in Figs. 2 and 4. Horizontal connector 126 is coupled to cover 24 in the same manner as connector 26 and communicates with port 60 of cover 24. When foam packing 30 is coupled to or positioned adjacent to cover 24, as shown in Fig. 6, horizontal member 126 is received within aperture 32 of packing 30. Further, tube 34 is received wholly or partially within slit 86 of packing when tube 34 is coupled to connector 126.

20 It is within the scope of this disclosure for foam packing 30 to be perforated to facilitate customizing the size of the foam to the wound cavity without using scissors. Further, foam packing 30 includes open-cell or closed-cell types of foam. For example, it is within the scope of this disclosure to include foam packing 30 made of hydrophobic or hydrophilic polyurethane foam or polyvinylalcohol foam.

25 As mentioned above, bandage 10 includes sealing layer or film 40 that is placed over packing 30 and around tube 34, as shown in Figs. 2 and 4. Film 40 may be substantially larger than the wound 16 or member 19 and packing 30 to provide an effective seal about the member 19 and the wound 16. Film 40 is provided to cover the entire wound 16 and to extend across and attach around tube 34 to the patient's healthy skin 42, as shown in Fig. 1. Preferably, film 40 is an occlusive or semi-occlusive material which allows water vapor to permeate through. Because of this characteristic, film 40 is referred to as Moisture Vapor Transmission Rate film or MVTR film. The products TEGADERM® brand sealing film made by 3M

-10-

Corporation and OPSITE FLEXIGRID® made by Smith & Nephew can be used for film 40, for example. The product OPSITE FLEXIGRID® is a semi-permeable film. Film 40 is approximately 0.003 inch (0.076 mm) thick, however, it is within the scope of this disclosure to include an occlusive or semi-occlusive film 40 having other
5 thickness. Film 40 is provided to create a sealed environment below the film 40 and around the wound 16 in which a vacuum or negative pressure can be maintained as provided by vacuum source 12.

Although this invention has been described in detail with reference to certain embodiments variations and modifications exist within the scope and spirit of
10 the invention as described and defined in the following claims.

-11-

CLAIMS:

1. A vacuum bandage connectable to a vacuum source and provided for use with a wound having a wound surface, the bandage comprising:
 - 5 a wound dressing member having a wound contacting surface, a top surface, a port configured for communication with the vacuum source, holes in the wound contacting surface configured for communication with a wound surface of the wound, and a passageway between the port and each hole, and
 - a pack adjacent to the top surface of the member, the pack including an
 - 10 aperture positioned about the port.
2. The bandage of claim 1, wherein the pack includes a bottom surface, a top surface, a side wall extending from the top surface to the bottom surface, and a slit in communication with the aperture and extending from the top surface to the bottom surface and from the aperture to the side wall.
- 15 3. The bandage of claim 2, wherein the pack is an opened-cell foam.
4. The bandage of claim 2, wherein the pack is a closed-cell foam.
5. The bandage of claim 1, wherein the pack further includes an adhesive layer to attach the pack to the top surface of the wound dressing member.
- 20 6. The bandage of claim 1, wherein the pack is removably coupled to the member.
7. The bandage of claim 1, wherein the member further includes a connector coupled to a top surface of the member and in communication with the port of the member, and wherein the connector is disposed in the aperture of the packing.
- 25 8. The bandage of claim 5, wherein the member is generally non-compressible and the pack is generally compressible.
9. The bandage of claim 8, wherein the member is made of a medical grade silicone and the pack is foam-like.
10. The bandage of claim 5, wherein the pack is removable from
- 30 the member while the member remains coupled to the vacuum source.
11. A foam packing for use with a vacuum bandage coupled to a vacuum source, the packing comprising:
 - a top surface, a bottom surface, and a side wall,

-12-

an aperture extending from the top surface to the bottom surface, the aperture configured to receive a vacuum tube of the vacuum bandage coupled to the vacuum source,

5 a slit in communication with the aperture and extending from the top surface to the bottom surface and from the aperture to the side wall, the vacuum tube being disposed at least in part in the slit, and

an adhesive layer on the bottom surface and configured to be spaced-apart from a wound surface of the wound.

12. The packing of claim 11, wherein the packing is made of an
10 open-celled foam.

13. The packing of claim 11, wherein the packing is made of a closed-cell foam.

14. The packing of claim 13, wherein the adhesive is silicone-based.

15 15. A vacuum bandage for use with a wound having an open wound surface and configured to be coupled to a vacuum source, the bandage comprising:

20 a wound dressing member having a wound contacting surface configured to contact the wound, the member including a plurality of holes formed in the wound contacting surface, a port configured to be coupled to the vacuum source, and a passageway from the port to each hole,

a foam pack disposed on the member, the pack including an aperture about the port of the member,

25 a tube received in the aperture of the foam pack, coupled to the port of the member, and configured to be coupled to the vacuum source, and

a sealing film covering the tube, foam pack, and member and configured to coupled to a patient's healthy skin surrounding the wound.

16. A bandage for use with a wound and a vacuum source, the bandage comprising:

30 an elastomeric member having a wound contacting surface adapted to contact a wound surface of the wound, the member having a port adapted to couple to a tube through which suction is communicated to the member, the member having

-13-

openings in the wound contacting surface and channels between each opening and the port, and

a foam pack positioned outside the flow channel and in contact with the member.

1/4



*FIG. 1*

FIG. 2



3/4




FIG. 3






FIG. 4

4/4



(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number
WO 2003/057071 A3

(51) International Patent Classification⁷: **A61M 35/00**

(US). PETROSENKO, Robert [CA/US]; 30 Belmont Place West, Batesville, IN 47006 (US).

(21) International Application Number:

PCT/US2002/041229

(74) Agent: CONRAD, Richard, D.; Barnes & Thornburg, 11 South Meridian Street, Indianapolis, IN 46204 (US).

(22) International Filing Date:

20 December 2002 (20.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/344,589 26 December 2001 (26.12.2001) US


(71) Applicant (for all designated States except US):
HILL-ROM SERVICES, INC. [US/US]; 1069 State Route 46 East, Batesville, IN 47006-9167 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,

[Continued on next page]

(54) Title: VACUUM BANDAGE PACKING



(57) Abstract: A vacuum bandage (10) is provided for use with a wound (16) having a wound surface (18). The bandage (10) is connectable to a vacuum source (12) and includes a wound dressing member (19) having a wound contacting surface (50), a top surface (70), and a port (60) configured for communication with the vacuum source (12). The wound dressing member (19) further includes holes (74) in the wound contacting surface (50) configured for communication with the wound surface (18) of the wound (16) and a passageway (56, 58) between the port and each hole. The vacuum bandage (10) further includes a pack (30) adjacent to the top surface (70) of the member (19). The pack (30) may include an aperture (32) positioned about the port (60).



TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY,

BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- with international search report

(88) Date of publication of the international search report:
15 January 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/41229

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61M 35/00

US CL : 604/289

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 604/289

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
Please See Continuation Sheet

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,636,643 A (ARGENTA et al.) 10 June 1997 (10.06.1997), column 6, line 46-	1, 7
---	column 7, line 23.	
Y		2-6 and 8-16
y	US 4,664,662 A (WEBSTER) 12 May 1987 (12.05.1987), see the entire document.	11-14
y	US 4,969,880 A (ZAMIEROWSKI) 13 November 1990 (13.11.1990), see the entire document.	1-6 and 15-16

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:	"T"
"A" document defining the general state of the art which is not considered to be of particular relevance	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

03 May 2003 (03.05.2003)

Date of mailing of the international search report

30 JUN 2003

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

Kim M. Lewis

Telephone No. 703.308.0858